

# VoIP V3 Indoor Intercom

The newest version of the CyberData SIP-enabled VoIP V3 Indoor Intercom is perfect for settings requiring two-way communication and secure access. The new processor allows for faster capabilities. One of many within our line of Power-over-Ethernet (PoE 802.3af) intercoms, the VoIP V3 Indoor Intercom has been utilized within nursing care and assisted living facilities, schools and universities, daycare facilities, apartment complexes and more, delivering a versatile, cost-efficient alternative to old analog intercoms.

## Typical Applications

- Access Control
- Door Entry Phone
- Emergency Phone
- Mass Notification

## Features

- PoE 802.3af enabled (Powered-over-Ethernet)
- SIP compliant
- Adaptive full-duplex voice operation
- Network web management
- Network adjustable speaker volume and microphone sensitivity
- Network downloadable firmware
- Concurrent SIP and multicast paging
- Dry relay contact for auxiliary control (controls external power)
- Peer-to-peer capable
- Door closure and tamper alert signal
- New Feature: Now supports SRST (Survivable Remote Site Telephony) in a Cisco environment.



## Specifications

Ethernet I/F	10/100 Mbps
Protocol	SIP RFC 3261 Compatible
Power Input	PoE 802.3af compliant or +12 to +24 VDC at 1000 mA (500 mA minimum)
Operating Temperature	-10° C to 50° C (14° F to 122° F)
Payload Types	G711, A-law and $\mu$ -law
Regulatory Compliance	FCC Class A, UL 60950
Dimensions	5" x 5" x 2.5" (H x W x D)
Warranty	2 years limited
Boxed Weight	1.2 lbs.
Part Number	*011211, RAL 9003, Signal White

\*This number replaces the 011111 number.

The following Intercom models are also available:



V3 Outdoor Intercom  
#011186

V3 Emergency Intercom  
#011209

V2 Indoor Keypad Intercom  
#011113

V3 Outdoor Keypad Intercom  
#011214

# VoIP V3 Indoor Intercom

